

Action 3NG





The Invacare® Action®3NG has been re-designed to ensure greater driving performance; a lightweight frame and high-quality components make for easy rolling and manoeuvrability. It enables easier assessment and adjusts for maximum mobility. The Action 3 manoeuvres smoothly due to its light rigid and well-balanced frame, and an ergonomic design that enables the user to become more independent.

- The Action®3NG introduces a new cross bar with a folding mechanism under the seat which improves stability and makes folding and unfolding even easier.
- Durability Adaptable and modular, the Action®3NG accommodates progressive changes in user needs.
- Transportable With a low transfer weight and foldable backrest, the Action®3NG is easy to fold and dismantle.
- Brake and Brake extension Fold the brake handle for easier side transfers.
- Length compensating leg support New option of elevating legrest offers optimal length compensation with the elevation stepped in approx. 3 – 5 degrees.
- Swing in / swing out footrest has an easy-to-operate quick release mechanism.
- Driving performance is enhanced with a choice of 20 rear wheel positions as standard.
- Users can set the rear wheel to Standard, Medium, Active or Amputee position.
- Total weight of 14kg addresses the need for improved handling, storage and transportation.
- The lowest transportation weight (without legrest, armrest and rear wheels)
 is 7.6 kg
- A magnesium castor attachment provides ease of angle adjustment and

○ Contract approved

ndis

Item Code:

05_122203108_0105_1_2

Wheelchair Manual -

Composite:05_417_0105_1_2 Click here for more information

Compliance

ISO 7176-7:1996



enhanced support. The use of the magnesium attachment reduces the weight of the chair by almost 400 grams.

Warranty Information

Frame & Crossbaraces: 2 YearsComponents: Limited 1 Year

Code	Display Name	Seat Depth	Seat Width	Safe Working Load
MWS449205	Action 3NG - 405mm	450 mm	405 mm	125 kg
MWS442915	Action 3NG - 505mm	450 mm	505 mm	125 kg
MWS449210	Action 3NG - Self Propelled - 18in (455mm) - 24in solid tyres	450 mm	450 mm	125kg